Post-Construction

Acknowledgement of Survey Monument Preservation

Monument Preservation post-construction activity

I,, a Landowner or Contractor with(Company)	
who performed work within Stanislaus County Right-of-Way hereby acknowledge my	
responsibility for monument preservation as required per Section 8771(a-f) of the Busin	ess and
Professions Code, within my scope of work and the bounds of the construction activity	
permitted by the Stanislaus County Encroachment Permit No. ENCR and	state
that to the best of my knowledge no Survey Monumentation has been disturbed.	
Signature of Landowner / Contractor	
Date	
Signature of County Encroachment Inspector	

Date

- 8771. (a) Monuments set shall be sufficient in number and durability and efficiently placed so as not to be readily disturbed, to ensure, together with monuments already existing, the perpetuation or facile reestablishment of any point or line of the survey.
- (b) When monuments exist that control the location of subdivisions, tracts, boundaries, roads, streets, or highways, or provide horizontal or vertical survey control, the monuments shall be located and referenced by or under the direction of a licensed land surveyor or licensed civil engineer legally authorized to practice land surveying, prior to the time when any streets, highways, other rights-of-way, or easements are improved, constructed, reconstructed, maintained, resurfaced, or relocated, and a corner record or record of survey of the references shall be filed with the county surveyor.
- (c) A permanent monument shall be reset in the surface of the new construction or a witness monument or monuments set to perpetuate the location if any monument could be destroyed, damaged, covered, disturbed, or otherwise obliterated, and a corner record or record of survey shall be filed with the county surveyor prior to the recording of a certificate of completion for the project. Sufficient controlling monuments shall be retained or replaced in their original positions to enable property, right-of-way and easement lines, property corners, and subdivision and tract boundaries to be reestablished without devious surveys necessarily originating on monuments differing from those that currently control the area.
- (d) The governmental agency performing or permitting construction or maintenance work is responsible for ensuring that either the governmental agency or landowner performing the construction or maintenance work provides for monument perpetuation required by this section.
- (e) It shall be the duty of every licensed land surveyor or licensed civil engineer legally authorized to practice land surveying to assist the governmental agency in matters of maps, field notes, and other pertinent records. Monuments set to mark the limiting lines of highways, roads, streets or right-of-way or easement lines shall not be deemed adequate for this purpose, unless specifically noted on the corner record or record of survey of the improvement works with direct ties in bearing or azimuth and distance between these and other monuments of record.
- (f) The decision to file either a corner record or a record of survey as required by subdivision (b) or (c) shall be at the election of the licensed land surveyor or the licensed civil engineer legally authorized to practice land surveying submitting the document.